

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **CEMENTO MATERICO**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Water based decorative paint based on lime. Professional and home use.****Uses advised against Uses other than those indicated**

1.3. Details of the supplier of the safety data sheet

Name **OIKOS S.P.A. a socio unico**
Full address **Via Cherubini 2**
District and Country **47043 Gatteo Mare (FC)**
Italia
Tel. **0547 681412**
Fax **0547 681430**

e-mail address of the competent person responsible for the Safety Data Sheet **certificazioniprodotti@oikos-group.it**

1.4. Emergency telephone number

For urgent inquiries refer to **NHS National Health Service 111****OIKOS S.P.A. a socio unico Company emergency number: 0547 681412**
Technical support - Monday to Friday from 8.00-13.00; 13:30 to 16:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: **Danger**

Hazard statements:

H318	Causes serious eye damage.
H315	Causes skin irritation.
EUH208	Contains: Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
	May produce an allergic reaction.

SECTION 2. Hazards identification ... / >>

Precautionary statements:

P102	Keep out of reach of children.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280	Wear protective gloves / eye protection / face protection.
P310	Immediately call a POISON CENTER / doctor / . . .
P101	If medical advice is needed, have product container or label at hand.
P264	Wash . . . thoroughly after handling.

Contains: Calcium dihydroxide

VOC (Directive 2004/42/EC) :

Decorative effect coatings.

VOC given in g/litre of product in a ready-to-use condition : 8,00
 Limit value: 200,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272I2008 (CLP)
Calcium dihydroxide		
CAS	1305-62-0	15 ≤ x < 20
EC	215-137-3	
INDEX		
Reg. no.	01-2119475151-45	
C12-C15 propoxylated alcohol		
CAS	74499-34-6	1 ≤ x < 1,5
EC	933-043-7	
INDEX		
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)		
CAS	55965-84-9	0,0005 ≤ x < 0,0014
EC	611-341-5	
INDEX	613-167-00-5	
Reg. no.	01-2120764691-48	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

Calcium dihydroxide

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	5				
VLEP	FRA	5				
WEL	GBR	5				
OEL	EU	1				
TLV-ACGIH		5				

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,49	mg/l
Normal value in marine water	0,32	mg/l
Normal value for water, intermittent release	0,49	mg/l
Normal value of STP microorganisms	3	mg/l
Normal value for the terrestrial compartment	1080	mg/kg

Health - Derived no-effect level - DNEL I DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	4		1		4		1	
	mg/m3		mg/m3		mg/m3		mg/m3	

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Predicted no-effect concentration - PNEC

Normal value in fresh water	3,39	µg/l
Normal value in marine water	3,39	µg/l
Normal value for fresh water sediment	27	µg/kg
Normal value for marine water sediment	27	µg/kg
Normal value of STP microorganisms	230	µg/l

Health - Derived no-effect level - DNEL I DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		110		90				
		µg/kg bw/d		µg/kg bw/d				
Inhalation	40	NPI	20	NPI	40	NPI	20	NPI
	µg/m3		µg/m3		µg/m3		µg/m3	
Skin		NPI	NPI	NPI		NPI	NPI	NPI

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

SECTION 8. Exposure controls/personal protection ... / >>

Protect hands with category III work gloves (see standard EN 374). The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	pasty liquid	
Colour	white	
Odour	Hydraulic binder	
Odour threshold	Not available	
pH	12,5-13,5	
Melting point / freezing point	Not available	
Initial boiling point	> 100 °C	
Boiling range	Not available	
Flash point	Not applicable	
Evaporation Rate	Not available	
Flammability of solids and gases	not flammable	
Lower inflammability limit	Not applicable	
Upper inflammability limit	Not applicable	
Lower explosive limit	Not applicable	
Upper explosive limit	Not applicable	
Vapour pressure	Not available	
Vapour density	Not available	
Relative density	1,65	
Solubility	Mixable in water	
Partition coefficient: n-octanol/water	Not available	
Auto-ignition temperature	Not applicable	
Decomposition temperature	Not available	
Viscosity	tixotropico	
Explosive properties	not applicable	
Oxidising properties	not applicable	

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

SECTION 10. Stability and reactivity ... / >>

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects
Metabolism, toxicokinetics, mechanism of action and other information

Calcium dihydroxide

ABSORPTION

The primary effect of calcium diide on health is local irritation caused by pH variation. Therefore, absorption is not a relevant parameter for the assessment of the effects of the substance.

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	Not classified (no significant component)
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	Not classified (no significant component)

Calcium dihydroxide

LD50 (Oral)

> 2000 mg/kg Rat (OECD 425)

LD50 (Dermal)

> 2500 mg/kg Rabbit (OCSE 402)

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LD50 (Oral)

> 64 mg/kg bw 64-561 (rat)

LD50 (Dermal)

1008 mg/kg bw (rat)

LC50 (Inhalation)

> 171 mg/m³ 171-2360 (rat)

C12-C15 propoxylated alcohol

LD50 (Oral)

> 2000 mg/kg Rat

SKIN CORROSION / IRRITATION

SECTION 11. Toxicological information ... />>

Causes skin irritation

Calcium dihydroxide
Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

Calcium dihydroxide
Causes severe eye injury

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Calcium dihydroxide
Does not meet the classification criteria for this danger class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
Reverse Bacterial Mutation Essay (Ames Test, OECD 471): Negative
Testing chromosomal aberrations on mammal cells: negative
Given that calcium is an omnipresent and essential element and that any variation of the lime-induced pH in watery means has no relevance, calcium dihydroxide is obviously devoid of any genotoxic potential. Classification by function of genotoxicity is not justified.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
Calcium (administered in the form of lactate) is not carcinogenic (experimental result, rat). The effect on pH on the product of calcium dihydroxide is free of any carcinogenic potential. Classification on the basis of carcinogenicity is not justified.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
Calcium (administered in the form of Ca carbonate) is not toxic for reproduction (experimental result, mouse). The effect on pH does not give rise to any reproductive risk. Human epidemiological data confirm that calcium dihydroxide is free of any potential toxicity. In both animal and clinical trials on different calcium salts, no effect has been identified on reproductive and developmental toxicity. v. also the Scientific Committee of Human Food (Anonymous, 2006). Therefore, calcium dihydroxide is not toxic for reproduction and/or development.
Classification on the basis of reproductive toxicity according to Regulation 1272/2008 is not necessary.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
It can irritate the airways

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
The toxicity of calcium through the oral exposure pathway is demonstrated by the increase in maximum tolerable intake levels (UL) for adults determined by the Scientific Committee of Human Food (SCF), where UL-2500 mg/die, equal to 38 mg/kg of weight/die, equal to 38 mg/kg of weight/die (individual weighing 70 kg) for calcium.
The toxicity of Ca(OH)₂ through contact with the skin is not considered relevant by virtue of the expected insignificant absorption through the skin and the fact that local irritation is the primary effect for health (pH variation).

SECTION 11. Toxicological information ... />>

The toxicity of Ca(OH)₂ by inhalation (local effect, mucous irritation), taking into account an average time weighed for an 8-hour shift, was determined by the Scientific Committee for Occupational Exposure Limits (SCOEL) in 1 mg/m³ of breathable dust. Therefore, the classification of Ca(OH)₂ on the basis of toxicity as a result of prolonged exposure is not necessarily

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
 Does not meet the classification criteria for this danger class

Calcium dihydroxide is classified as irritating to the skin and airways, and carries the risk of serious eye injury. The limit of occupational exposure for the prevention of sensory irritation at the local level and the reduction of lung function parameters as effects is OEL (8 hours) - 1 mg/m³ of breathable dust.

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

Calcium dihydroxide
 LC50 (96h) on sea fish: 457 mg/l
 LC50 (96h) on sea invertebrates: 158 mg/l
 NOEC (72 hours) on freshwater algae: 48 mg/l
 TOXICITY ON MICROORGANISMS, ES BACTERIA
 At high concentration, through temperature and pH rise, calcium dihydroxide is used for disinfection of sewer sludge.
 NOEC (14 days) for sea invertebrates: 32 mg/l
 EC10/LC10 or NOEC on soil macro-organisms: 2000 mg/kg soil dw
 EC10/LC10 or NOEC on soil microorganisms: 12000 mg/kg soil dw
 NOEC (21 days) on terrestrial plants: 1080 mg/kg
 GENERAL EFFECT
 Acute effect of pH. Although this substance is useful for correcting water acidity, excess over 1 g/l can be harmful to aquatic organisms. A value of pH > 12 will decrease rapidly and as a result of dilution and carbonation.

Calcium dihydroxide	
LC50 - for Fish	50,6 mg/l/96h freshwater fish
EC50 - for Crustacea	49,1 mg/l/48h invertebrate
EC50 - for Algae /Aquatic Plants	184,57 mg/l/72h alga

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	
LC50 - for Fish	> 190 µg/l 190-330
EC50 - for Crustacea	> 7 µg/l 7-160
EC50 - for Algae /Aquatic Plants	> 6,3 µg/l 6,3-27,3
Chronic NOEC for Fish	46,4 µg/l 35 days
Chronic NOEC for Crustacea	> 111 µg/l 11.1-1050

C12-C15 propoxylated alcohol	
LC50 - for Fish	> 100 mg/l/96h Pimephales promelas
EC50 - for Crustacea	> 100 mg/l/48h Daphnia pulex
EC50 - for Algae /Aquatic Plants	> 100 mg/l/72h Selenastrum capricornutum

12.2. Persistence and degradability

SECTION 12. Ecological information ... / >>

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Rapidly degradable

C12-C15 propoxylated alcohol
NOT rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Calcium dihydroxide
Calcium diidhydroxide is a moderately soluble substance and therefore has poor mobility in most soils.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 16. Other information ... / >>

- LEGEND:- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
 - CE50: Effective concentration (required to induce a 50% effect)
 - CE NUMBER: Identifier in ESIS (European archive of existing substances)
 - CLP: EC Regulation 1272/2008
 - DNEL: Derived No Effect Level
 - EmS: Emergency Schedule
 - GHS: Globally Harmonized System of classification and labeling of chemicals
 - IATA DGR: International Air Transport Association Dangerous Goods Regulation
 - IC50: Immobilization Concentration 50%
 - IMDG: International Maritime Code for dangerous goods
 - IMO: International Maritime Organization
 - INDEX NUMBER: Identifier in Annex VI of CLP
 - LC50: Lethal Concentration 50%
 - LD50: Lethal dose 50%
 - OEL: Occupational Exposure Level
 - PBT: Persistent bioaccumulative and toxic as REACH Regulation
 - PEC: Predicted environmental Concentration
 - PEL: Predicted exposure level
 - PNEC: Predicted no effect concentration
 - REACH: EC Regulation 1907/2006
 - RID: Regulation concerning the international transport of dangerous goods by train
 - TLV: Threshold Limit Value
 - TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
 - TWA STEL: Short-term exposure limit
 - TWA: Time-weighted average exposure limit
 - VOC: Volatile organic Compounds
 - vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
 - WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
 This document must not be regarded as a guarantee on any specific product property.
 The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
 Provide appointed staff with adequate training on how to use chemical products.

SECTION 16. Other information ... / >>

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 15.