

# Cera per Stucco

SCHEDA TECNICA  
cs/01

## Technical characteristics

CERA per STUCCO is a decorative wax in paste form, created to exalt the shine of stucco. Thanks to its quick and simple, one coat, application by trowel or sponge, it is possible to obtain excellent marble effects whilst still respecting the technique and the natural feel of the stucco finish on which the Cera per Stucco is applied. The additives in the product facilitate its application and make it easier to polish. Cera per Stucco protects the surface on to which it is applied making it rub resistant. It is non inflammable, has no added formaldehyde and is friendly to both humans and the environment.

## The application

Dilution	Ready to use
Yield	80/100 m <sup>2</sup> /l.
Application tools	Inox steel trowel, synthetic sponge by OIKOS
Base	Decorative, lime based stucco
Application temperature	+5°C ÷ +36°C (with relative humidity not exceeding 80%)
Drying time until touch dry	1 h (temperature = 20°C with relative humidity at 75%)
Total drying time	20 ÷ 24 days (temperature = 20°C with relative humidity at 75%)
Tools cleaning	Water

## Ideal use

Polishing and protection of interior walls and furnishings coated with decorative stucco.

## Surface preparation

Wait at least 6-8 hours after the application of the last coat of stucco and in any case until it is completely dry.

## Application method

Apply a single, even coat of CERA per STUCCO using a float (inox steel trowel). On uneven surfaces it is possible to apply the product using a synthetic sponge. To further enhance the shine, after 24 hours it is possible to polish the surface using a soft cloth. Attention: avoid leaving too much product on the surface because this could cause the formation of light haloes.

## The product

Composition	Based on precious waxes and water
Specific weight	0.97 kg/l +/- 3%
PH Viscosity	Paste
Storage temperature	++5°C ÷ +36°C. Keep from freezing
Reaction to fire	Negative if applied on a non inflammable base; water based material with dry thickness of less than 0,600 mm
Emission limits of Volatile Organic Compounds (VOC), in accordance with the norm 2004/42/CE	Classification: A/I; VOC: 0 g/l (max); Limit phase I (from 1.1.2007):300 g/l, Limit phase II (from 1.1.2010):200 g/l
Colours	Bianco
Packaging	1 Litre

## Safety information

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is considered to be a non-dangerous substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements.

## Note

The company Oikos Spa guarantees, to the best of its own technical and scientific knowledge, that the information contained in this technical data sheet is correct. Notwithstanding that indicated above, Oikos takes no responsibility for the results obtained through the use of this product in as much as it is not possible for Oikos to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.



the ecological paint

**OIKOS S.P.A. a socio unico**  
Via Cherubini, 2  
47043 Gatteo Mare (FC)  
info@oikos-group.it

**ITALIA**  
tel. +39 0547.681412  
**INTERNATIONAL**  
tel. +39 0547.681460