

Technical Qualities

TOPMATT is a formaldehyde-free, professional ecological paint for interiors, providing excellent coverage and a pleasant matt effect. Ready to use, to prevent any dilution errors. The special formula guarantees excellent breathability for surfaces and also well-being in internal spaces. Its excellent coverage makes it easy to apply, helping to hide any flaws in application and touch-ups thanks to its even, matt finish. It is ideal for spray painting, which makes application much faster, optimising work time and avoiding any problems caused by join lines.

- VAPOUR PERMEABILITY
- HIGH COVERAGE
- MATT



Ideal Use

Interiors.

Surface preparation

Clean the surface to be painted, removing any loose or flaking material. Only on powdering or highly absorbent surfaces apply a coat of the acrylic sealers CRILUX or NEOFIX by OIKOS. In the event that it is necessary to increase the coverage of the application cycle, apply the pigmented primer IL PIGMENTATO by OIKOS. Wait at least 6 hours before proceeding to apply finish products.

Application method

Shake the product well before use. Apply two coats of TOPMATT leaving 4 ÷ 6 hours between coats. The product is ready to use but it is possible to add up to 5% drinkable water to make application easier.

To obtain an even finish, application is recommended by spray or good quality roller for interior walls. Brush application is possible, paying attention when brushing out the product.

Safety Information

The product contains no heavy metals such as chrome or lead or toxic solvents, aromas and chlorates. The product does not give rise to dangerous polymerisations. The product is not considered as dangerous if used in a technically correct manner. Normal precautionary measures for the handling of water based paints are suggested. For the storage and movement of the material, no particular considerations are required; the containers, residual material or eventual spillages should be collected, using inert absorbent materials such as sand or earth and then disposed of in line with the regional or national regulations that are in force. Transportation should be carried out in observance of international agreements.

Application

Dilution	Roller and brush: ready to use, max 5% drinkable water. Airless: up to 10-12% (Nozzle 0,013-0,017 inch, 120-140 Atm) HVLV: up to 10-12% (nozzle 1,6-1,8 mm)
Yield	3,5 – 5 m ² /l in two coats
Application tools	Roller, brush or spray
Primers and Basecoats	Crilux, Neofix, Il Pigmentato by OIKOS
Application temperature	+5°C ÷ +36°C (with relative humidity not exceeding 80%)
Drying time until touch dry	2 ÷ 4 h (temperature = 20°C with relative humidity at 75%)
Drying time until washable	7 days (temperature = 20°C with relative humidity at 75%)
Total drying time	36 h (temperature = 20°C with relative humidity at 75%)
Time until possible to paint over	6 h (temperature = 20°C with relative humidity at 75%)
Tools cleaning	Water

Product

Composition	Vinyl emulsion in water dispersion with organic and inorganic pigments as well as special additives to aid application and formation of the surface film.
Specific weight	1,55 kg/l +/- 3%
pH	8 ÷ 9,5
Viscosity	7000-9500 CPS Brookfield (RVT 20 revs/min. at 25°C)
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Resistance to washing	Class 4 (UNI EN ISO 11998:2006)
Water vapour permeability Sd	HIGH: Sd 0,004 m (UNI EN ISO 7783-2:2012)
Emission limits of Volatile Organic Compounds (VOC), according to the regulation 2004/42/CE	Classification: A/a; VOC: < 30 Phase II limits (from 1.1.2010): 30 g/l
Colours	White + colours from colour chart
Packaging	Liters 1-4-10-14 (upon request 1000 litres)

Specifications

Carefully clean the surface to be painted, removing any loose or flaking material. In the presence of powdering or highly absorbent surfaces, apply an acrylic based sealer such as CRILUX or NEOFIX by OIKOS. Should it be necessary to increase the coverage of the application cycle, apply a pigmented primer such as IL PIGMENTATO by OIKOS. After 6 hours apply two coats of an ecological, professional paint for interiors, with high coverage and matt finish, formaldehyde-free such as TOPMATT by OIKOS. All should be realised in respect of application normatives at a cost of per m² inclusive of material and application.

Advice for use and conservation

Shake well before use. To dilute, only use drinkable water. The undiluted product can be conserved in clean, sealed, adequately sized containers and protected from freezing or excessive heat. Between different types of products, the perception of White (or any other colour) can seem different to the human eye. This is important to understand in the event that one wished to apply 2 different products of the same colour,

on the same wall. It is advised to not use different batches of the same coloured product on the same wall.

Note

Oikos Spa guarantees that the information contained in this technical data sheet is supplied to the best of its technical and scientific knowledge. In spite of this, Oikos does not accept any responsibility for the results achieved through the use of its products in as the company has no control over the application methods used and has no way to check or verify them. As such we recommend to check the suitability of each product for the use to which it is to be put.